

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
30 October 2003 (30.10.2003)

PCT

(10) International Publication Number  
**WO 03/090449 A2**

- (51) International Patent Classification<sup>7</sup>: **H04N**
- (21) International Application Number: **PCT/US03/12177**
- (22) International Filing Date: **21 April 2003 (21.04.2003)**
- (25) Filing Language: **English**
- (26) Publication Language: **English**
- (30) Priority Data:  
**60/374,280**      **19 April 2002 (19.04.2002)**      **US**
- (71) Applicant (for all designated States except US): **THOMSON LICENSING S.A.** [US/US]; 2 Independence Way - Suite 2, Princeton, NJ 08540 (US).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

(72) Inventor; and


(75) Inventor/Applicant (for US only): **GEORGE, John, Barrett** [US/US]; 11408 Lakeshore Drive E., Carmel, IN 46033 (US).

Published:

— without international search report and to be republished upon receipt of that report

(74) Agents: **TRIPOLI, Joseph, S. et al.**; c/o Thomson Licensing Inc., 2 Independence Way - Suite 2, Princeton, NJ 08540 (US).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: **FOCUS VOLTAGE CONTROL ARRANGEMENT WITH ULTOR VOLTAGE TRACKING**

(57) Abstract: A video display apparatus includes a cathode ray tube having an ultor terminal for developing an ultor voltage at the ultor terminal to produce a beam current. The ultor voltage has voltage fluctuations in a presence of changes in the beam current. A resistive voltage divider is coupled to a source of a first high voltage and to a focus terminal of the cathode ray tube for producing at the focus terminal a second high voltage including voltage fluctuations. The voltage fluctuations are indicative of the voltage fluctuations of the ultor voltage to provide for focus voltage tracking. An amplifier responsive to a periodic correction signal is capacitively coupled via a capacitor having a value of 33 picofarad to the focus terminal. A dynamic focus voltage that varies, in accordance with a variation of a beam landing location, is produced at the focus terminal.